



TASKI Swingo 755 Specs

	Metric		Imperial	
Taski 755B ECO				
Theoretical Performance	1290	Sq.m/h	13886	Sq.ft./h
Working Width	43	cm	17.0	in.
Squeegee Width	69	cm	27.2	in.
Solution Tank Nominal	40	L.	8.8	gal.
Recovery Tank Nominal	40	L	8.8	gal.
Nominal Consumption	900	Watts	900	Watts
Rated Voltage	24	V	24	V
Battery Capacity	50-70	Amp/hrs	50-70	Amp/hrs
Battery Autonomy Nominal	2	h	2	h
Machine Wt. Ready for Use - pwr	155	Kg	341.7	lbs.
Dimensions (Length)	1160	mm	45.7	in.
Dimensions (Width)	475	mm	18.7	in.
Dimensions (Height)	1195	mm	47.0	in.
Turning Circle	1120	m	44.1	in.
Brush System	430 x1	mm	16.9	x1 in.
Brush Pressure - pwr	40	kg	88.2	lbs.
Working Speed - pwr	3	km/h	1.9	mph

Cable Length of integrated Battery Charger	N/A	m	N/A	yds.
Noise Level	58	dB(A)	58	dB(A)

Taski 755B Power

Theoretical Performance	self -propelled 1935 Sq.m/h		self -propelled 20828 Sq.ft./h	
Working Width	43	cm	17.0	in.
Squeegee Width	69	cm	27.2	in.
Solution Tank Nominal	40	L.	8.8	gal.
Recovery Tank Nominal	40	L	8.8	gal.
Nominal Consumption	900	Watts	900	Watts
Rated Voltage	24	V	24	V
Battery Capacity	50-70	Amp/hrs	50-70	Amp/hrs
Battery Autonomy Nominal	2	h	2	h
Machine Wt. Ready for Use - pwr	160	Kg	352.7	lbs.
Dimensions (Length)	1160	mm	45.7	in.
Dimensions (Width)	475	mm	18.7	in.
Dimensions (Height)	1195	mm	47.0	in.
Turning Circle	1120	m	44.1	in.
Brush System	430 x1	mm	16.9	x1 in.
Brush Pressure - pwr	43	kg	94.8	lbs.
Working Speed - pwr	4.5	km/h	2.8	mph
Cable Length of integrated Battery Charger	N/A	m	N/A	yds.
Noise Level	58	dB(A)	58	dB(A)

